

PATENT APPLICATION

Attorney Docket No. A01172US (98538/2)

TITLE OF THE INVENTION

Method and Apparatus for Consolidating Earth Strata

5 INVENTOR: BODEGOM, Dirk Albertus, a citizen of the Netherlands,
of Meidoornstraat 18, 2861 VJ Bergambacht, The Netherlands

CROSS-REFERENCE TO RELATED APPLICATIONS

Priority of Dutch patent application no. 1016329, filed in
the Netherlands on 4 October 2000, is hereby claimed. That
10 patent application is hereby incorporated by reference.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not applicable

REFERENCE TO A "MICROFICHE APPENDIX"

Not applicable

15 BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a method and apparatus for
consolidating earth strata.

U.S. Patents Nos. 4,471,540; 4,643,615; and 6,254,308;
20 International Publication No. WO 00/50696; and Published Japanese
Patent Application No. 10278292, published as publication no.
2000104242 on 11 April 2000, are incorporated herein by
reference.

When the bearing capacity of a soil is insufficient for
25 carrying out a civil engineering project, such as the
construction of a rail road or a motorway, it may be increased
by forcedly driving out/withdrawing water from the weak earth
strata (clay, peat). By withdrawing water the soil material will
be pressed against each other and thus obtain an increased
30 bearing capacity. As a consequence, the volume of soil body will
decrease.

Forced consolidation techniques have been known for a long
time. Nowadays drainage ribbons are often used, which are driven

() ()

vertically into the ground with great force by means of a drive-in lance. On top of the ground level, incorporating the projecting end portions of the ribbons, a sand body is placed over which an airtight membrane is arranged. In the sand body a
5 drainage pipe has been accommodated, to which a pump is connected, with which water and air is withdrawn from the sand body and thus from the drainage ribbons and the areas surrounding it. The weight of the sand body increases the pressure of the water to be withdrawn, in order to accelerate the process.

10 However, an objection is that during the forced consolidation process the terrain, due to the presence of the membrane, is not available for (preparations for) construction activities. A membrane moreover has to be bought, arranged and guarded and mostly be removed and discharged in a flow of waste
15 material.

It is an object of the invention to improve on this. The present invention provides a method for consolidating an earth stratum situated in a subgrade by withdrawing water that is present. The method comprises the stepwise arrangement from the
20 surface of the soil, at some depth, of vertical draining means, such as drainage strips, in the earth stratum, the arrangement of horizontal drainage means, such as drainage pipes, in the upper area of the earth stratum and connecting them to the vertical drainage means for water transfer between them, the
25 arrangement of an air sealing layer directly over the horizontal drainage means and the closing of the surface of the soil, as well as the connection of the horizontal drainage means to a pump for discharge of the water and air. In this way the upper load relatively increases to the atmospheric pressure and the terrain
30 is made available again for other activities. The pump may be very effectively active, as the sealing prevents drawing in of air from above the drainage means, at least reduces it to a large degree.

Preferably a trench is made from the ground surface and the vertical drainage means are arranged from the bottom of the trench. As a result the drainage means need not be pressed through an upper layer, and their length may be limited to the minimum necessary.

In an advantageous embodiment the trench is being made by means of a plough that is arranged on a device, a vertical drainage means being arranged by means of said device as well, and the horizontal drainage means are each time arranged after that until the next vertical drainage means has to be arranged. Thus both the vertical and horizontal drainage means are preferably arranged in a continuous progress of a process.

Preferably simultaneously with the arrangement of the horizontal drainage means or immediately after that, the air sealing layer is being arranged by means of the device as well, as a result of which the time of processing is further minimized.

Preferably the air sealing layer is being arranged by removing soil material from the trench walls and pressing it on the horizontal drainage means. In this way use is made of sealing material that is already present, which is particularly possible in cases of clay or loamy soil.

Alternatively the air sealing layer can be arranged by arranging a sealing foil layer or plastic material such as, for instance bentonite, on the horizontal drainage means.

Preferably the air sealing layer is arranged by means of the device.

It is further preferred that the trench is finally closed off with soil material up to approximately the original surface. Then as well no supply of extra soil material will be necessary.

In a further development of the method according to the invention the vertical drainage means are taken from a supply, and after having been arranged are separated by cutting through at a level above the trench bottom, so that the upper portion is

available for contact with the preferably elongated or tubular horizontal drainage means. The cutting through preferably takes place in the device, so that a good performance is ensured.

From another aspect the invention provides an apparatus for
5 use in forced consolidation, comprising a device provided with means for moving them in horizontal direction, over the ground surface, with means for making a trench from the ground surface down to at least just below the upper side of the earth stratum to be consolidated, with means for the stepwise supplying of a
10 vertical drainage ribbon from a supply and driving it into the earth stratum, and means for supplying a horizontal drainage means in the trench bottom.

Preferably the device is further provided with means for cutting through the drainage ribbon at a level above the trench
15 bottom. The means for cutting through preferably comprises a movable blade and an anvil for said blade, said blade preferably having been arranged on an arm of a lever rotatable about a horizontal center line, the other arm of said lever being connected to a vertically active hydraulic cylinder, preferably
20 accommodated in the trench-making means. In this way a high cutting power can be achieved with low (horizontal) occupation of space, as the stroke length of the cylinder is not limited by horizontal limitations.

The trench-making means is preferably a plough, which at its
25 rear side is provided with means for removing soil material from the trench walls and for pressing it downward, for forming an air sealing layer over the horizontal drainage means, or with means for arranging foil or bentonite, at least (initially) plastic sealing material.

30 Preferably, at its rear side the plough is provided with means for supplying the horizontal drainage means, particularly from a supply roll, in the trench, so that they are situated, as it were, at the free shadow side.

It is furthermore preferred that means are provided for pivoting the plough about a horizontal axis of rotation, between a trench-making active position and an upwardly tilted moving position and vice versa. On the one hand this facilitates transport, on the other hand it can promote initial penetration of the plough.

The invention will be elucidated on the basis of an exemplary embodiment shown in the attached drawings, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

For a further understanding of the nature, objects, and advantages of the present invention, reference should be had to the following detailed description, read in conjunction with the following drawings, wherein like reference numerals denote like elements and wherein:

Figure 1 is a side view of the preferred embodiment of the apparatus of the present invention;

Figures 1A-C show several possible states of the apparatus according to figure 1, amongst others a fully collapsed state (figure 1C);

Figure 2 is a partial side view of the preferred embodiment of the apparatus of the present invention showing the plough part of the apparatus;

Figures 2A-H show several details and cross-sections, partially and schematically, of the plough part of figure 2;

Figures 3A and 3B schematically show the portion in the plough part of the figures 2A-2C with which a drainage ribbon can be cut through;

Figures 4A and 4B illustrate a possible way of connecting the drainage ribbon to the lance of the apparatus of figure 1; and

Figure 5 schematically shows a project carried out with an apparatus according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

Figure 1 shows the preferred embodiment of the apparatus of the present invention, designated generally by the numeral 1. The apparatus 1 can include a hydraulic excavating machine 40 in order to form a kind of driving rig, which is common in driving vertical drainage ribbons into a ground. The hydraulic machine 40 is supported on ground level 41, and has an arm or boom 110 which is hinged to the machine at 70a. At the outer end, the arm 110 is connected to a U-shaped bracket 12 at hinge 71. A second connection is provided between machine 40 and U-shaped bracket 12 consisting of a piston/cylinder assembly 4a that extends between hinge 70c on the machine 40 and hinge 73 on the bracket 12. Hinge 73 is located above hinge 71. A further connection is provided between the arm 110 and the machine 40 with piston cylinder assembly 4d, in order to move the arm 110 up and down. Piston/cylinder assembly 4d is connected at hinge 72 to boom 110 and at hinge 70b to machine 40.

A king's post 2 is connected to both ends of the U-shaped bracket 12 by means of a first connection, consisting of a hinge 75, a piston/cylinder assembly 4c, a hinge 74 and a bracket 3a, located at a distance above the lower end of the post 2, and by means of a second connection, consisting of a hinge 79 and a bracket 3b located at the lower end of the post 2. A lance 5 is supported by the post 2 and can be moved up and down along the post 2 in the directions P by means of means that are known per se and not further shown.

By way of background information, as illustrated in figures 4A and 4B, the lower end of the lance 5 is connected to an end of drainage ribbon 9, which is unwound from a supply roll (not shown) arranged on the post 2. The lower end of the ribbon 9 is passed in the direction J through a U-bracket 38 fixed to a plate 37, and then the plate 37 is moved against the lower end of the lance 5 in the direction K. When the lance 5 is urged into the

() ()

ground (direction L) , the plate 37, which laterally extends from the lance 5, will bend according to arrows M to form inclined anchoring lips 39. When a length of drainage ribbon has been pressed into a ground to be consolidated by means of the lance 5, the lance 5 is lifted again. Due to the anchoring lips 39, the lower end of ribbon 9 will be held in the ground and stay in its place. The drainage ribbon will be cut through at ground level or above it after letting the lance pass upwards along the kings post, after which the new end of the drainage ribbon is connected again to the lance, for instance by means of an anchor, for a subsequent processing step.

The U-shaped bracket 12 forms a support for a plough 6 too. This plough 6, which will be described in detail, is hinged to the bracket 12 at 77, spaced apart from hinge 79. In addition, the plough 6 is connected to the bracket 12 by means of a piston/cylinder assembly 4b, which is hinged to the bracket 12 at 76 and to the plough 6 at hinge 78, between hinges 77 and 71. Hinge 76 is located between hinges 75 and 73.

The plough 6 has a front edge 7 and a rear side 8. At its lower end, the front edge 7 may be provided with a nose, but it is left out in the figures.

Due to the various hinges 70-79 and the piston/cylinder assemblies 4a-d, the machine 40, the arm or boom 110, the post 2 and the plough 6 may be set at different angles with respect to each other, as illustrated in figures 1A-C. In the upright position of figure 1A the piston/cylinder assembly 4d has been extended somewhat, and assembly 4a has been operated to maintain the orientation of bracket 12 as compared to figure 1. Two other positions have been indicated in figure 1A, that is for the post 2 a lying orientation by swinging the post 2 in direction S, realized by extending assembly 4c, and for the plough 6 a halfway swung back (direction T) orientation, realized by extending assembly 4b, all while maintaining the orientation of bracket 12.

() ()

In figure 1B the post 2 has been left out, and the plough 6 has been swung to a horizontal orientation, while maintaining the orientation of bracket 12.

In figure 1C, piston/cylinder assemblies 4a and 4d have been operated to swing the post 2, the bracket 12 and the plough 6 as a unity from the orientation of figure 1 into a horizontal, transportation orientation.

Turning now to figure 2, at its front edge 7, the plough has a sharp front edge with flanks 7a, 7b. These flanks merge into side plates 113a,b, defining an inner space shielded from the soil and providing strength to the plough 6. In this inner space, the plough 6 is provided with a vertical passage 15, at the lower end of which a schematically indicated ribbon cutter 16 has been arranged, which in an exemplary embodiment is shown in detail in the figures 3A and 3B.

The cutting mechanism 16 shown in figure 3A and 3B is arranged to be active at the lower end of vertical passage 15, near its lower opening 15a. Figure 3A schematically shows a drainage ribbon 9 vertically extending through the passage 15, at the moment the lance has already been drawn and the drainage ribbon 9 therefore has been inserted into the ground sufficiently deep.

The ribbon cutting mechanism 16 comprises an anvil 22 attached in a holder 23 fixedly arranged on the plough 6, against which anvil a blade 21 can be brought with great force for cutting the drainage ribbon 9. The blade 21 has been attached to a lever 24, which is hingedly attached in the plough 6 at the location of pivot pin 30, and which by means of pin 29 has been attached to the end of a piston rod 27 of cylinder 26, which itself has been attached with the other end to an attachment block 28 fixedly arranged on the plough 6.

When a drainage ribbon 9 has to be cut through, the cylinder 26 is excited with means that are not further shown, so that the

piston rod 27 is urged downwards in the direction A. As a result the pin 29 is moved downwards, in which as a result of the hinging attachment of the upper end of the cylinder 26 to the block 28 some deflection to the rear is possible, so that a
5 fluent rotational movement about the pivot pin 30 is possible. Thus the lever 24 is rotated anti-clockwise in the direction B, until the blade 21, as can be seen in figure 3B, has separated the drainage ribbon 9 into a portion 9a that is left behind in the ground and a portion 9b that can be arranged at another
10 location. The arrangement shown with vertical operation cylinder 26 and lever 24 for converting a vertical movement into a more or less horizontal cutting movement is efficient as regards occupation of space and power transmission.

At its upper side the plough 6 is provided with attachment
15 eyes 77a and 78a, serving to accommodate hinges 77 and 78, respectively.

At the rear side 8, the plough 6 is provided with a pipe 10, having an entrance 19 at its upper end and a smoothly curved portion 10a at its lower end, which curved portion 10a is cut
20 open in the upper portion of its circumference and ends in portion 10b, where also the lower portion of its circumference has been cut away (notice the cross sections of figures 2C and 2D). The end portion 10b is horizontally oriented and defines exit 20 which is oriented horizontally rearwards.

25 Parallel to pipe 10, directly rearwards of it, extends a supply for an air-tight sealing foil strip or sheet 99, when the application of such a foil would be needed. The supply comprises a support 90 for a supply roll 98 of a foil strip 99. The strip 99 is guided over idle roller 97 into a downward direction, where
30 it engages about a pipe 91 having a circular cross-section. A small distance below pipe 91 a pipe 93 has been arranged about the pipe 91 to form an annular channel therewith for the foil strip 99 (see figure 2B).

As can be seen in figure 2A, the lower ends of the circular pipes 91,93 are received in plate 120 which forms a part of bracket 121 that is fixed to the plough 6. Only the inner pipe 91 continues, and this pipe gradually merges into a U-shaped profile 94 realized at the lower end of bracket 121, just above the curved track 95. As can be seen in figures 2A and 2F, the space around profile 94 is sidewardly bounded by plates 14a,b, to the rear by plate 14c and in front by plate 14d. The U-shaped profile 94 has a bottom 80 and two side walls 84a,b, as can be seen in the cross-section of figure 2C.

The side walls 14a,b are downwardly continued in curved downward extension plates 82a,b in curved track 95 to form a U-shaped channel 83 for the foil strip 99. As can be seen in figure 2C, this channel is delimited at its bottom by the pipe 10a, or, at pipe 10b, by the drainage pipe travelling through pipe 10 at the same speed.

Thus, in the downward direction of travelling, the foil 99 is transferred from a more or less circular shape into a U-shape, the legs of the U-shaped foil strip 99 being folded about the bottom 80 and the side walls 84a,b and being laterally confined by the downward extensions 82a,b of the plates 14a,b.

As can be seen in figures 2, 2A, 2E and 2H, the plough 6 is provided with a pair of scraping blades 101,102, forming part of an inverted U-shaped scraper 100, attached to the lower end of the bracket 121 and defining a horizontal, upwardly confined passage Y (figure 2E). The scraper 100 has two inclined scraper blades 101, 102a and 101, 102b and upper wall 103/104, wherein the blades 102a, b and wall 104 converge towards each other and urge the soil flowing rearwards through the scraper 100 downward.

The scraping blades 101a, b have slanted front edges 105a, b (figures 2A, 2E, 2H) which project sideways from the plates 113a, 113b to cut soil from the walls (45a, 45b in figure 2E) of the trench made by the plough. This cut out soil will then be

able to fall on the foil strip 99 that travels just below it. The scraper 100 may be left out in case no foil strip 99 is applied.

Below the scraper 100, the plough 6 is provided with a pair of blades 86a, 86b extending obliquely upwards and sideways and
5 having front edges 106a, 106b that are inclined upwards and rearwards and upper edges 87a, 87b (figures 2A, 2E and 2G). These blades 86a, 86b make a cut into the walls of the trench made by the plough in order to make an incision or discontinuity in these walls, so that the stability of the walls below the incision may
10 not be affected by the soil scraper and presser 11 yet to be described, which is active on the soil above the incision.

Reference is made to figures 2 and 2A, in which the soil scraping and pressing and soil filling blades 11 attached to the rear 8 of the plough 6 has been illustrated. The soil
15 scraper/presser 11 is positioned behind the scraper 100 and the blades 87a, 87b. It regards a substantially inverted U-shaped pressing profile 60, which at its front at the location of hinge 53 is hingedly attached to the plough 6, in particular bracket 121. At its upper side, the profile 60 is provided with a block
20 50 with stop 51 which abuts against a stop bolt 52 threadingly attached to bracket 121 by means of a pair of nuts 54. By adjusting the nuts 54 the length of projection of bolt 52 can be adjusted, and therewith the angle of orientation of the profile 60 with respect to the plough 6. The profile 60 has two legs 61a,
25 62a and 61b, 62b and an upper wall 66, wherein the upper wall 66 is inclined rearwards and downwards, and the leg portions 62a, 62b converge to each other, so as to define a narrowing passage or tunnel for the soil. As can be seen in figures 2A and 2E, the edges 64,65 of the legs 61, 62 are downwardly and rearwardly
30 inclined. The level of the edges 65a,b is just below the level of the lower edges of blade legs 101,102. The wall 66, and therewith the legs 61, 62, however, extend laterally beyond the blade legs 101, 102 and the blades 86a, 86b. Moreover, the level

of the edges 65a, 65b is slightly higher than the level of the upper edges 87a, 87b of the blades 86a, 86b.

In figure 5 a picture at a given moment is given of a project in which the apparatus according to the invention is being used. The excavating machine 40 holds the king's post 2 straight up and provides the necessary power and operation lines. The project was started on the left-hand side in the drawing. The hydraulic machine 40 has moved itself over the ground level 41, underneath which a sand layer 42 is situated. At larger depth a sand layer 44 is situated between relatively weak -for instance clay or loamy- earth strata 43 and 45. In order to be able to carry out a project, such as the construction of a rail road or motorway, at the ground level it is necessary to reinforce the earth stratum 43, which takes place by accelerated consolidation, by letting water present in the layer 43 escape from it. This technique is known per se.

One starts by rotating (direction T) the plough 6 from the position shown left in figure 1B to a vertical position, during which movement the plough is able to penetrate the soil. A plough nose may be an aid here. If required a small excavation may be made locally. The plough 6 may have a height of several meters (for example, 2 meters or more), in any case sufficient to amply extend into the earth stratum 43.

When the plough 6 has been brought on the right location for arranging a vertical drainage ribbon, the apparatus is operated to press a drainage ribbon 9a in the earth stratum 43 by means of lance 5, down to the wanted depth. The lance 5 need not penetrate the sand layer 42 here, but instead easily penetrates the free passage 15 within the plough 6. After the lance 5 has been lifted again and the drainage ribbon 9 has been cut through by the cutting mechanism at about the level of line X in Figure 5, the machine 40 is driven one step backwards, in which the plough 6 is pulled along in the direction D, while making a

trench. During that movement a bendable drainage pipe 36 is supplied from a supply that is not further shown on king post 2, in which the pipe moves through the passage 10, 10a, 10b and exits from the horizontally oriented opening 20 in the direction H (see Figure 2A). The end of the perforated drainage pipe 36 is connected to an unperforated pipe portion 36a, which leads to a deep well pump 31 above ground level, which later on is able to discharge water (and air) in the direction F. The supplying of the drainage pipe 36 at the rear side of the plough 6 is relative: the drainage pipe that is already in the trench remains there, and the plough moves in the direction D.

At the next location where a drainage ribbon has to be arranged, one proceeds as with drainage ribbon 9a and thus the drainage ribbons 9b, 9c, 9d, 9e etc. are arranged stepwise. With all interim movements in the direction D the horizontal drainage pipe 36 is extended stepwise, until the situation shown in figure 4 has been reached. During the movements, the part of the drainage ribbon that extends between the cutting mechanism 16 and the lower side of the plough 6 is horizontally spread on the trench bottom as a result of engaging against the outer bend 10a of the passage 10, and on the thus horizontally turned portion 9a' (see figure 5) the horizontal drainage pipe 36 has come down, as a result of which a direct contact between both drainage elements is possible for quick passing on of water. When the wanted end of the horizontal extension of the pipe 36 has been reached, the pipe can be cut at depth and sealed at the end or connected to a perforated pipe portion that is connected to a second pump, so that in case of larger drainage lengths water can be discharged in two directions.

Alternatively this connection can be realised in a casing of granular material. To that end, simultaneously with either the drainage pipe or with a separate pipe, a granular material is supplied via pipe 10 to a space formed by lower side plough, bend

10a and the vertical ribbon.

In order to let the drainage arrangement be as efficient as possible, use is made of an underpressure system in which according to the invention it is prevented that false air is being drawn in, particularly in the area above the drainage pipe. In order to let the drainage pipe be active as much as possible in downward direction, the contact area with the drainage ribbons, first an incision is made in the trench wall by means of the blades 86a,b, after which the U-blade 60 extends with horizontal portion 66 in those incisions made and soil material below there in the trench wall is cut vertically by the legs 61a, b and after that is removed from the trench wall by the converging legs 62a, 62b and urged downwards by wall 66. During the movement steps in the direction D of the plough 6, the material is thus pressed and compacted on and around the upper half of the circumference of the horizontal drainage pipe 36 by the pressing blade 60, so that an as it were airtight layer 46 is situated on the pipe 36. The reversed U-shape of blade 60 and the stop 52 here promote the realization of the airtight sealing.

When the work has been completed the plough 6 can be removed from the trench by tilting about hinge 77. alternatively, the assembly of plough 6, bracket 12 and post 2 can be lifted. In that case, the hinged connection of the scraper/presser 11, 60 at 53 permits the scraper/presser 11, 60 to rotate towards a more vertical orientation in which the lifting movement is facilitated. In addition, by such an orientation it is avoided that the walls of the trench are severely damaged, which would otherwise result in local collapse of these walls and loosened soil falling on the drain, due to which a leakage path might be realized.

In case the type of soil is less cohesive or substantially granular, the foil 99 can be used to provide an air tight seal on the pipe 36. Here, the scraper 100 and the parts for the

supply of the foil strip 99 are used, the strip 99 being supplied at the same speed as the drainage pipe 36 in the direction I and H, respectively (figure 2 and 2A). The scraper cuts the soil from the trench walls, crumbles it and urges it downwards to let it
5 fall on the foil strip 99 which is then already more or less horizontal. Thus it is ensured that the strip has a proper position on the upper side of the drainage pipe before the pressing and filling blade 60 becomes active in the area concerned. The foil 99 used can be a composite one, such as a
10 sandwich foil of an upper layer and a lower layer of polypropylene for strength, and an air tight foil in between these layers.

When making the trench the plough can be hindered by high density types of soil, or by obstacles of a natural or artificial
15 nature. In order to remove or minimize that hinder the plough can be equipped with means known per se for breaking off the cohesion of the soil and/or obstacles or displacing them. In one embodiment the plough at its front edge 7 is provided with one or several blades that are vertically movable over the entire
20 height of the cut surface. When necessary these blades make an upward and downward movement.

Alternatively for making the trench, the trench-making device can be provided with a ground cutter in the portion in front of a vertical passage of the lance/the ribbon. It strongly
25 resembles a chain saw and may consist of an endless chain which may or may not be provided with teeth and/or scrapers. A chain here runs in the centre of the device about a drive wheel at the upper side of the device to a turn wheel at the lower side of the device. The shafts of the chain wheels are perpendicular to the
30 direction of travel of the device whereas the chain runs in the plane of the direction of movement of the device. Here the device is furthermore provided with the means described earlier on for supplying the pipe and possibly the U-shaped soil closing blades.

The movement of the chain may take place in continuous rotating movement or in an up and downwardly oscillating movement. In a special embodiment several chains may run side by side possibly having an opposing direction of movement.

5 Alternatively the plough can be provided with one or several vibrating mechanisms to let the plough make a pulsating movement in the propelling movement as well as transverse to it.

It is noted that the methods discussed can also be used from a pontoon on a subaqueous soil.

10

PARTS LIST

The following is a list of suitable parts and materials for the various elements of the preferred embodiment of the present invention.

	PART NO.	DESCRIPTION
15	1	apparatus
	2	kings post
	3a	bracket
	3b	bracket
	4a	piston cylinder ssembly
20	4b	piston cylinder assembly
	4c	piston cylinder assembly
	4d	piston cylinder assembly
	5	lance
	6	plough
25	7	front edge
	7a	flank
	7b	flank
	8	rear side
	9	drainage ribbon
30	9a	ribbon
	9a'	horizontally turned portion
	9b	ribbon
	9c	ribbon

	9d	ribbon
	9e	ribbon
	10	pipe
	10a	curved pipe portion
5	10b	pipe end portion
	11	soil scraper/presser
	12	u-shaped bracket
	14a	plate
	14b	plate
10	14c	plate
	14d	plate
	15	vertical passage
	15a	lower opening
	16	ribbon cutting mechanism
15	19	entrance
	20	exit
	21	anvil blade
	22	anvil
	23	holder
20	24	lever
	26	cylinder
	27	piston rod
	28	attachment block
	29	pin
25	30	pivot pin
	31	deep well pump
	36	drainage pipe
	36a	unperforated portion
	37	plate
30	38	u-shaped bracket
	39	anchoring lips
	40	excavating machine
	41	ground level

	42	sand layer
	43	earth stratum
	44	sand layer
	45a	wall
5	45b	wall
	46	airtight layer
	50	block
	51	stop
	52	stop bolt
10	53	hinge location
	54	nut
	60	presser
	61	leg
	61a	leg
15	61b	leg
	62	leg
	62a	leg
	62b	leg
	64	edge
20	65	edge
	65a	edge
	65b	edge
	66	upper wall
	70a	hinge
25	70b	hinge
	70c	hinge
	71	hinge
	72	hinge
	73	hinge
30	74	hinge
	75	hinge
	76	hinge
	77	hinge

	77a	attachment eye
	78	hinge
	78a	attachment eye
	79	hinge
5	80	bottom
	82a	curved downward extension plate
	82b	curved downward extension plate
	83	u-shaped channel
	84a	side wall
10	84b	side wall
	86a	blade
	86b	blade
	87a	upper edge
	87b	upper edge
15	90	support
	91	inner pipe
	93	pipe
	94	u-shaped profile
	95	curved track
20	97	idle roller
	98	supply roll
	99	foil strip
	100	scraper
	101	scraping blade
25	101a	scraping blade
	101b	scraping blade
	102	scraping blade
	102a	scraping blade
	102b	scraping blade
30	103	wall
	104	wall
	105a	slanted front edge
	105b	slanted front edge

	106a	front edge
	106b	front edge
	110	boom
	113a	side plate
5	113b	side plate
	120	plate
	121	bracket
	A	direction arrow
	B	direction arrow
10	D	direction arrow
	F	direction arrow
	H	direction arrow
	J	direction arrow
	K	direction arrow
15	L	direction arrow
	M	direction arrow
	P	direction arrow
	S	direction arrow
	T	direction arrow
20	X	line
	Y	passage

The foregoing embodiments re presented by way of example only; the scope of the present invention is to be limited only by the following claims.